


RESİM	AÇIKLAMA			
	<p>Curtis kontrolörü; 24V80AH lityum pil; yandan çekmeli pil tasarımı; AC sürüş motoru; EPS direksiyon; tam boyutlu koruma camı; platformlu ve kolçaklı; PU tekerlekler; harici akıllı şarj cihazı</p>	<p>MİMA MB2030 2 TON 3.000 MM ASANSÖRLÜ ELEKTRİKLİ İSTİFLEME MAKİNASI</p>		

2. TESLİMAT : HEMEN TESLİM - İŞLETME TESLİM

3. GARANTİ SÜRESİ: 2 yıl 2000 SAAT (Hangisi önce dolarsa) Aküler 3 yıl 6000 SAAT (Hangisi önce dolarsa)

Standard

1,1	Manufacturer			MİMA
1,2	Model			MB2030
1,3	Power type			Battery
1,4	Driving style			Stand on
1,5	Rated load	Q(kg)		2000
1,6	Load center	C(mm)		600
1,7	Front overhang	x(mm)		737
1,8	Wheelbase	y(mm)		1390

Weights

2,1	Service Weight(incl.battery)	kg		1115
2,2	Bridge load at full load, drive side/load-bearing side	kg		1149/1966
2,3	Bridge load at unload, drive side/load-bearing side	kg		807/308

Wheels

3,1	wheel type			PU
3,2	Load wheel size	mm		Φ80x70
3,3	Drive wheel size	mm		Φ230x75
3,4	Stabilizing wheel size	mm		Φ125x50
3,5	Number of wheels,front/rear(x=drive wheel)			4/1x+2
3,6	Wheel base,drive-bearing side	b10(mm)		630/770 ^[3]
3,7	Wheel base, load-bearing side	b11(mm)		490/380 ^[3]

Size

4,1	Mast closed height	h1(mm)		2025
4,2	Free lift height	h2(mm)		/
4,3	Lift height	h3(mm)		3000
4,4	Mast extended height with load-backrest	h4(mm)		3506
4,5	Handle height(min/max)	h14(mm)		1100/1390 ^[1]
4,6	Minimum height of fork surface	h13(mm)		90
4,7	Overall length,Pedal retracted	l1(mm)		2110 ^[2]
4,8	Overall width	b1/b2(mm)		850/1000 ^[3]
4,9	Fork size	l/e/s(mm)		1150/190/56
4,10	Fork outside width	b5(mm)		680/570 ^[3]
4,11	Mast ground clearance	m1(mm)		30
4,12	Aisle width (pallet 1000x1200)Load center C500mm	Ast(mm)		2490
4,13	Right-angle stacking aisle width (pallet 800x1200)Load center C600mm	Ast(mm)		2450
4,14	Turning radius,Pedal retracted	Wa(mm)		1655 ^[2]

Function

5,1	Driving speed, load/unloaded	km/h		5.0/6.0
5,2	Lifting speed,load/unloaded	mm/s		65/115
5,3	Lowering speed,load/unload	mm/s		85/115
5,4	Maximum climbing ability, load/unloaded (S2-5min)	%(tanθ)		≤6/≤8
5,5	Braking method			Electromagnetic

Drive

6,1	Drive motor power (S2-60min)	kw		1,5
6,2	Lift motor power, (S3-15%)	kw		2
6,3	Battery, voltage/rated capacity	V/Ah		24/210*
6,4	Battery weight	kg		200
6,5	steering system			Electronic steering ^[1]

Others

7,1	Battery replacement method			Side pull
7,2	Mast series			Single cylinder duplex mast

