


RESİM	AÇIKLAMA		
	<p><b>Curtis Kontrol; AC Yürüyüş Sistemi; PU Tekerler; Koruyucu Cam 570mm çatal genişliği; Orantılı Kaldırma Hızı Kontrolü;24V/200AH Lityum Akü.EPS</b></p> <p><b>MİMA MBC1645 1.6 TON 4.500 MM ASANSÖRLÜ ELEKTRİKLİ İSTİFLEME MAKİNASI</b></p>		

#### AÇIKLAMA :

TESLİMAT : HEMEN TESLİM - İŞLETME TESLİM

GARANTİ SÜRESİ: 2 yıl 2000 SAAT (Hangisi önce dolarsa)Aküler 3 yıl 6000 SAAT(Hangisi önce dolarsa)

#### ÖZELLİKLER

1,1	Manufacturer		<b>MİMA</b>	
1,2	Model		<b>MBC1645</b>	
1,3	Power type		Battery	
1,4	Driving style		Walkie	
1,5	Rated load	Q(kg)	1600	
1,6	Load center	C(mm)	600	
1,7	Wheelbase	y(mm)	1290	

#### AĞIRLIK

2,1	Service Weight(incl.battery)	kg	1150	
-----	------------------------------	----	------	--

#### TEKER

3,1	wheel type		PU	
3,2	Load wheel size	mm	Φ80×70	
3,3	Drive wheel size	mm	Φ230×75	
3,4	Stabilizing wheel size	mm	Φ125×50	
3,5	Number of wheels,front/rear(x=drive wheel)		4/1x+1	
3,6	Wheel base,drive-bearing side	b10(mm)	530	
3,7	Wheel base, load-bearing side	b11(mm)	490	

#### ÖLÇÜ

4.1	Mast closed height	h1(mm)	2825	
4.2	Free lift height	h2(mm)		
4.3	Lift height	h3(mm)	4500	
4.4	Mast extended height with load-backrest	h4(mm)	5000	
4.5	Handle height(min/max)	h14(mm)	700/1300	
4.6	Minimum height of fork surface	h13(mm)	90	
4.7	Overall length	l1(mm)	1990	
4.8	Overall width	b1/b2(mm)	820	
4.9	Fork size	l/e/s(mm)	1150/190/58	
4.10	Fork outside width	b5(mm)	680*	
4.11	Mast ground clearance	m1(mm)	30	
4.12	Aisle width (pallet 1000x1200)Load center C500mm	Ast(mm)	2375	
4.13	Right-angle stacking aisle width (pallet 800x1200)Load center C600mm	Ast(mm)	2375	
4.14	Turning radius	Wa(mm)	1490	

#### FONKSİYON

5,1	Driving speed, load/unloaded	km/h	5.0/6.0	
5,2	Lifting speed,load/unloaded	mm/s	90/130	
5,3	Lowering speed,load/unload	mm/s	110/130	
5,4	Maximum climbing ability, load/unloaded (S2-5min)	%(tanθ )	≤6/≤12	
5,6	Braking method		Electromagnetic	

#### SÜRÜŞ

6,1	Drive motor power (S2-60min)	kw	1,5	
6,2	Lift motor power, (S3-10%)	kw	2	
6,4	Battery, voltage/rated capacity	V/Ah	24/210* (Side pull)	
6,5	Battery weight	kg	180	
6,6	steering system		Mechanical steering	

#### DİĞER

7,1	Battery replacement method		Side pull	
7,2	Mast series		Single cylinder duplex mast	

