


RESİM	AÇIKLAMA			
	1500 KG 3300 MM Zapi controller; 24V/80AH free maintenance battery; DC driving motor; mechanical steering; H channel steel mast; PU wheels; External intelligent charger			MİMA MBD1530 1.5 TON 3.000 MM ASANSÖRLÜ ELEKTRİKLİ İSTİFLEME MAKİNASI

AÇIKLAMA :

TESLİMAT : HEMEN TESLİM - İŞLETME TESLİM

GARANTİ SÜRESİ: 2 yıl 2000 SAAT (Hangisi önce dolarsa) Aküler 3 yıl 6000 SAAT (Hangisi önce dolarsa)

Electric pallet stacker MBD

1,1	Manufacturer		MİMA	MİMA
1,2	Model		MBD12	MBD15
1,3	Power type		Battery	Battery
1,4	Driving style		Walkie	Walkie
1,5	Rated load	Q(kg)	1200	1500
1,6	Load center	C(mm)	500	500
1,7	Wheelbase	y(mm)	1200	1200
Weights				
2,1	Service Weight(incl.battery)	kg	560	590
Wheels				
3,1	wheel type		PU	PU
3,2	Load wheel size	mm	Φ80×70	Φ80×70
3,3	Drive wheel size	mm	Φ210×70	Φ210×70
3,4	Stabilizing wheel size	mm	Φ125×50	Φ125×50
3,5	Number of wheels,front/rear(x=drive wheel)		2/1x+1	2/1x+1
3,6	Wheel base,drive-bearing side	b10(mm)	/	/
3,7	Wheel base, load-bearing side	b11(mm)	400	400
Size				
4.1	Mast closed height	h1(mm)	2030	2030
4.2	Lift height	h3(mm)		
4.3	Mast extended height with load-backrest	h4(mm)	3510	3510
4.4	Handle height(min/max)	h14(mm)	800/1200	800/1200
4.5	Minimum height of fork surface	h13(mm)	85	85
4.6	Overall length	l1(mm)	1750	1750
4.7	Overall width	b1(mm)	800	800
4.8	Fork size	l/e/s(mm)	1150/160/60	1150/160/60
4.9	Fork outside width	b5(mm)	560*	560*
4.10	Mast ground clearance	m1(mm)	30	30
4.11	Aisle width (pallet 1000x1200)Load center C500mm	Ast(mm)	2050	2050
4.12	Right-angle stacking aisle width (pallet 800x1200)Load center C600mm	Ast(mm)	2100	2100
4.13	Turning radius	Wa(mm)	1440	1440
Function				
5,1	Driving speed, load/unloaded	km/h	3.5/4	3.5/3.6
5,2	Lifting speed,load/unloaded	mm/s	110/180	73/107
5,3	Lowering speed,load/unload	mm/s	130/160	85/115
5,4	Maximum climbing ability, load/unloaded (S2-5min)	%(tanθ)	3/6	3/6
5,5	Braking method		Electromagnetic	Electromagnetic
Drive				
6,1	Drive motor power (S2-60min)	kw	0,75	0,75
6,2	Lift motor power, (S3-15%)	kw	2	2
6,3	Battery, voltage/rated capacity	V/Ah	2x12/80	2x12/80
6,4	Battery weight	kg	50	50
6,5	steering system		Mechanical steering	Mechanical steering
Others				
7,1	Battery replacement method		Battery	Battery
7,2	Mast series		Single cylinder duplex mast	Single cylinder duplex mast
DİĞER				
7,1	Battery replacement type		Hoisting	Hoisting
7,2	Lithium battery voltage/capacity	V/Ah	24/200	24/200
6,6	Direksiyon sistemi			
Other				
7,2	AC kaldırma motoru, (S3-15%)	kw		

