


RESİM	AÇIKLAMA			
	<p>Curtis Kontrol; AC Yürüyüş ve Kaldırma Sistemi; İz yapmayan beyaz dolgu lastik; side shift; OPS Koruma Sistemi; Hidrolik Direksiyon; Lüks Koltuk; Mavi ışık dikiz aynası ve takım çantası;80v 500 A İnci Akü;80V 80A Redresör</p> <p>MİMA MK45 - MK50 4.5 TON ve 5 TON STANDART VE TRIPLEKS ASANSÖR SEÇENEKLİ ELEKTRİKLİ FORKLİFT</p>			

AÇIKLAMA :

TESLİMAT : HEMEN TESLİM - İŞLETME TESLİM

GARANTİ SÜRESİ: 2 yıl 2000 SAAT (Hangisi önce dolarsa)Aküler 3 yıl 6000 SAAT(Hangisi önce dolarsa)

Standard

			MİMA	MİMA
1,1	Manufacturer		MİMA	MİMA
1,2	Model		MK45	MK50
1,3	Power Type		Battery	Battery
1,4	Operation Type		Driving Style	Driving Style
1,5	Rated Capacity	Q(kg)	4500	4999
1,6	Load Center	C(mm)	500	500
1,8	Front Overhand	x(mm)	530	530
1,9	Wheelbase	y(mm)	2000	2000

Weight

2,1	Service Weight(incl.battery)	kg	6800	7100
-----	------------------------------	----	------	------

Wheel

3,1	Wheel Types		Solid rubber tyre	Solid rubber tyre
3,2	Load Wheel	mm	21×8-9	21×8-9
3,3	Drive wheel	mm	250-15	250-15
3,5	Number of wheels,front/rear(x=drive wheel)		2x/2	2x/2
3,6	Wheel tread,drive side	b10(mm)	1225	1225
3,7	Wheel tread,load side	b11(mm)	1025	1025

Size

4,1	Mast tilting	$\alpha/\beta(^{\circ})$	6/11	6/11
4,2	Mast closed height	h1(mm)	2180	2180
4,3	Free lift height	h2(mm)	150	150
4,4	Lift height	h3(mm)	3000	3000
4,5	Mast extended height with load-backrest	h4(mm)	4040	4040
4,7	Overhead guard height	h6(mm)	2250	2250
4,8	Seat height	h7(mm)	1230	1230
4,19	Overall length	L1(mm)	4060	4060
4,20	Length to fork face	L2(mm)	2990	2990
4,21	Overall width	b1/b2(mm)	1470/1350	1470/1350
4,22	Fork size	l/e/s(mm)	1070/150/50	1070/150/50
4,23	Installation level		3A	3A
4,24	Fork carriage width	b3(mm)	1380	1380
4,25	Fork outside width	b5(mm)	320~1320	320~1320
4,31	Mast ground clearance	m1(mm)	120	120
4,32	Body ground clearance	m2(mm)	120	120
4,34	Aisle width for pallet 1000*1200	Ast(mm)	4490	4490
	Aisle width for pallet 800*1200	Ast(mm)	4690	4690
4,35	Turning radius	Wa(mm)	2690	2690

Function

5,1	Driving speed(load/unload)	km/h	12/13	12/13
5,2	Lifting speed(load/unload)	mm/s	200/220	200/220
5,3	Lowering speed(load/unload)	mm/s	270/290	270/290
5,5	Traction capacity(load/unload)(S2-5min)	N	15400	15680
5,8	Max.Gradeability(load/unload)(S2-5min)	%(tan θ)	15/15	15/15
5,10	Brake type		Mechanical hydraulic	Mechanical hydraulic

Drive

6,1	Driving motor(S2-60min)	kw	AC16.6	AC16.6
6,2	Lifting motor(S3-15%)	kw	AC15	AC15
6,4	Battery voltage/capacity	V/Ah	80/560	80/630
6,5	Battery weight	kg	1390	1690
6,6	Steering system		Hydraulic type	Hydraulic type

Other

7,1	Lithium battery configuration	V/Ah	80/450	80/450
7,2	AC lifting motor, (S3-15%)	kw	AC10	AC10

